

Reciprocating Saw LXT®

DJR186Z

18V • 0 – 2 800 min⁻¹ • 32 mm

Efficient basic reciprocating saw

An efficient reciprocating saw for spark-free cutting of metal and demolition work. Stroke length of 32 mm and stroke rate of 0 – 2 800 min⁻¹ with continuous control from the switch. Quick-release blade attachment. Tool only, battery and charger not included.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Strokes per Minute (SPM)	0 - 2800 min ⁻¹
Length of Stroke	32 mm
Max. Cutting Capacity in Wood (90°)	255 mm
Max. Cutting Capacity in Steel Pipe	130 mm
Sound Power Level (L _{WA})	95 dB(A)
Sound Pressure Level (L _{pA})	84 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	13,0 m/s ²
Vibration Level (3 axes), Cutting Chipboard	13 m/s ²
Vibration Level (3 axes), Cutting Wood	12,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²

User benefits

- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381806640

Link to product - www.makitauk.com



Related products

Optional AC

B-55566

Reciprosaw Blade 100 x 1,25 mm

B-55588

Reciprosaw Blade 228 x 1,25 mm

B-49834

Reciprosaw Blade 152 x 1,25 mm

B-49856

Reciprosaw Blade 305 x 1,25 mm

B-05169

Reciprosaw Blade 152 x 0,9 mm

B-55588-10

Reciprosaw Blade 228 x 1,25 mm



B-55572

Reciprosaw Blade 152 x 1,25 mm





B-55594

Reciprosaw Blade 305 x 1,25 mm





B-49840

Reciprosaw Blade 228 x 1,25 mm





821620-5

Plastic Carrying Case





B-55572-10

Reciprosaw Blade 152 x 1,25 mm





B-55594-10

Reciprosaw Blade 305 x 1,25 mm



Other

User manual

Parts drawing